

PLATINUM WASH 16R PRO™

SKU# EPW499



Photometric Data

Specifications are subject to change without any prior written notice.

Distance	m	ft	m	ft	m	ft
	7.5	24.6	10	32.8	12.5	41.0
MIN ZOOM						
3° Beam Diameter	0.39	1.3	0.52	1.7	0.65	2.1
7° Field Diameter	0.93	3.1	1.24	4.1	1.55	5.1
	lux	fc	lux	fc	lux	fc
Full ON	55,850	5188	31,770	2951	20,080	1865
MAX ZOOM						
14° Beam Diameter	1.83	6.0	2.44	8.0	3.05	10.0
22° Field Diameter	2.91	9.5	3.88	12.7	4.85	15.9
	lux	fc	lux	fc	lux	fc
Full ON	5,795	538	3,328	309	2,120	197
MIN ZOOM - LIGHT FROST						
6° Beam Diameter	0.76	2.5	1.02	3.3	1.27	4.2
13° Field Diameter	1.65	5.4	2.2	7.2	2.75	9.0
	lux	fc	lux	fc	lux	fc
Full ON	16,300	1514	9,250	859	5,935	551
MAX ZOOM - LIGHT FROST						
14° Beam Diameter	1.86	6.1	2.5	8.2	3.1	10.2
27° Field Diameter	3.57	11.7	4.76	15.6	5.95	19.5
	lux	fc	lux	fc	lux	fc
Full ON	3,795	353	2,186	203	1,440	134
MIN ZOOM - HEAVY FROST						
11° Beam Diameter	1.47	4.8	1.96	6.4	2.45	8.0
22° Field Diameter	2.94	9.6	3.92	12.9	4.9	16.1
	lux	fc	lux	fc	lux	fc
Full ON	4,071	378	2,325	216	1,109	103
MAX ZOOM - HEAVY FROST						
23° Beam Diameter	3.06	10.0	4.08	13.4	5.1	16.7
44° Field Diameter	5.61	18.4	7.48	24.5	9.35	30.7
	lux	fc	lux	fc	lux	fc
Full ON	1,230	114	717	67	385	36

ELATION | PLATINUM WASH 16R PRO™ | Photometric Data