

ELATION® CUEPIX STRIP WW™							
DMX Channel Values / Functions (10 DMX Channels)							
Specifications are subject to change without any prior written notice.							
*Control of COB Modules depends on the Flip setting.							
MODE / CHANNEL						VALUE	FUNCTION
1 CH	2 CH	5 CH	6 CH	8 CH	10 CH		
	1					0-255	*COB MODULES 1-5 0 to 100%
1	2					0-255	MASTER DIMMER Intensity 0 to 100%
		1	1	1	1	0-255	*COB MODULE 1 0 to 100%
		2	2	2	2	0-255	*COB MODULE 2 0 to 100%
		3	3	3	3	0-255	*COB MODULE 3 0 to 100%
		4	4	4	4	0-255	*COB MODULE 4 0 to 100%
		5	5	5	5	0-255	*COB MODULE 5 0 to 100%
					6		MACROS
						0-20	NORMAL
						21-42	DREAM Macro
						43-64	METEOR Macro
						65-87	FADE Macro
						88-110	CHANGE Macro
						111-123	FLOW ! Macro
						124-146	FLOW 2 Macro
						147-169	FLOW 3 Macro
						170-192	FLOW 4 Macro
						193-255	NO FUNCTION
					7		MACRO SPEED
						0-255	SLOW to FAST
			6	6	8		MASTER DIMMER
						0-255	Intensity 0 to 100%
				7	9		FLASH / STROBE
						0-255	Flash / Strobe Effect SLOW to FAST
				8	10		DIMMING CURVE MODES
						0-41	STANDARD
						42-84	STAGE
						85-127	TV
						128-170	ARCHITECTURAL
						171-213	THEATRE
						214-255	Default to Unit Setting

troits
ELATION | CUEPIX STRIP WW™ | dmx

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu