

ELATION® LEVEL Q7 IP™
DMX Channel Values / Functions - VERSION 2 (17 DMX Channels)

Specifications are subject to change without any prior written notice.

MODE / CHANNEL					VALUE	FUNCTION
4CH	5CH	7CH	12CH	17CH		
1	1	1	1	1		RED [ALL LEDs]
					0-255	(0-Black , 255-100% RED)
				2		RED FINE ADJUSTMENT [ALL LEDs]
					0-255	RED Fine Adjustment
2	2	2	2	3		GREEN [ALL LEDs]
					0-255	(0-Black , 255-100% GREEN)
				4		GREEN FINE ADJUSTMENT [ALL LEDs]
					0-255	GREEN Fine Adjustment
3	3	3	3	5		BLUE [ALL LEDs]
					0-255	(0-Black , 255-100% BLUE)
				6		BLUE FINE ADJUSTMENT [ALL LEDs]
					0-255	BLUE Fine Adjustment
4	4	4	4	7		WHITE [ALL LEDs]
					0-255	(0-Black , 255-100% WHITE)
				8		WHITE FINE ADJUSTMENT [ALL LEDs]
					0-255	WHITE Fine Adjustment
		5	5	9		COLOR CORRECTION [ALL LEDs]
					0	NO Function
					1-255	(1-2,700K, 255-7,200K)
				10		COLORS
					0	NO Function
					1-7	Color Macro 1
					8-15	Color Macro 2
					16-23	Color Macro 3
					24-31	Color Macro 4
					32-39	Color Macro 5
					40-47	Color Macro 6
					48-55	Color Macro 7
					56-63	Color Macro 8
					64-71	Color Macro 9
					72-79	Color Macro 10
					80-87	Color Macro 11
					88-95	Color Macro 12
					96-103	Color Macro 13
					104-111	Color Macro 14
					112-119	Color Macro 15
					120-127	Color Macro 16
					128-135	Color Macro 17
					136-143	Color Macro 18
					144-151	Color Macro 19
					152-159	Color Macro 20
					160-167	Color Macro 21
					168-175	Color Macro 22
					176-183	Color Macro 23
					184-191	Color Macro 24
					192-199	Color Macro 25
					200-207	Color Macro 26
					208-215	Color Macro 27
					216-223	Color Macro 28
					224-231	Color Macro 29
					232-239	Color Macro 30
240-247	Color Macro 31					
248-255	Color Macro 32					

ELATION | LEVEL Q7™ | dmX traits

ELATION® LEVEL Q7 IP™
DMX Channel Values / Functions - VERSION 2 (17 DMX Channels)

Specifications are subject to change without any prior written notice.

MODE / CHANNEL					VALUE	FUNCTION
4CH	5CH	7CH	12CH	17CH		
			7	11		INTERNAL PROGRAM MACROS
					0	NO Function
					1-30	Internal Program Macro 1
					31-60	Internal Program Macro 2
					61-90	Internal Program Macro 3
					91-120	Internal Program Macro 4
					121-150	Internal Program Macro 5
					151-180	Internal Program Macro 6
					181-210	Internal Program Macro 7
					211-255	Internal Program Macro 8
			8	12		SHUTTER, STROBE
					0-31	LEDs OFF
					32-63	LEDs ON
					64-95	STROBE Effect SLOW to FAST
					96-127	LEDs ON
					128-159	Pulse Effect in Sequences
					160-191	LEDs ON
					192-223	Random STROBE Effect SLOW to FAST
					224-255	LEDs ON
	5	7	9	13		DIMMER INTENSITY / INTERNAL PROGRAM MACRO SPEED*
					0-255	Dimmer Intensity 0 to 100% / Speed SLOW to FAST* *Only When Internal Program Macro is used in 12CH and 17CH modes.
				14		DIMMER INTENSITY FINE
					0-255	Dimmer Intensity FINE Adjustment
			10	15		DIMMING MODES
					0-20	STANDARD
					21-40	STAGE
					41-60	TV
					61-80	ARCHITECTURAL
					81-100	THEATRE
					101-255	Default to Unit Setting
			11	16		COLOR ENABLE
					0-189	NO Function
					190-255	Enable (Turn ON) EDIT WHITE BALANCE Mode
			12	17		COLOR MODE
					0-190	NO Function
					190-254	EDIT (Set) a New WHITE BALANCE
					255	STORE (Save) a New WHITE BALANCE

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu