


ACL 360 MATRIX™

SKU# ACL001



Photometric Data

Specifications are subject to change without any prior written notice. 07/15



	1 m 3.3 ft		2 m 6.6 ft		3 m 9.8 ft		4 m 13.1 ft		5 m 16.4 ft	
14° Beam Diameter	0.28	0.9	0.60	2.0	0.96	3.1	1.27	4.2	1.58	5.2
19° Field Diameter	0.33	1.1	0.69	2.3	1.03	3.4	1.38	4.5	1.72	5.6
	lux	fc	lux	fc	lux	fc	lux	fc	lux	fc
RED LEDs	15,116	1,404	9,537	886	7,623	708	5,847	543	4,518	420
GREEN LEDs	33,054	3,071	25,468	2,366	18,072	1,679	12,970	1,205	9,849	915
BLUE LEDs	5,263	489	4,632	430	3,873	360	3,095	288	2,201	204
WHITE LEDs	39,711	3,689	30,574	2,840	23,545	2,187	16,999	1,579	12,883	1,197
FULL ON	77,344	7,185	70,370	6,537	54,413	5,055	40,505	3,763	29,722	2,761

ELATION | ACL 360 MATRIX™ | Photometric Data

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu