

ELATION® VOLT Q5E™					
DMX Channel Values / Functions VERSION 2 (12 DMX Channels)					
Doc Date	2/6/2015	Soft Ver	≥ 1.0.3		
Specifications are subject to change without any prior written notice.					
MODE / CHANNEL				VALUE	FUNCTION
4 CH	5 CH	11 CH	12 CH		
1	1	1	1	0-255	RED Red (0-100%)
2	2	2	2	0-255	GREEN Green (0-100%)
3	3	3	3	0-255	BLUE Blue (0-100%)
4	4	4	4	0-255	WHITE White (0-100%)
		5	5	0	COLOR CORRECTION NO Function
				1-255	1 = 2,700K / 255 = 7,200K
					COLOR MACROS
				0	NO Function
				1-7	Color Macro 1
				8-15	Color Macro 2
				16-23	Color Macro 3
				24-31	Color Macro 4
				32-39	Color Macro 5
				40-47	Color Macro 6
				48-55	Color Macro 7
				56-63	Color Macro 8
				64-71	Color Macro 9
				72-79	Color Macro 10
				80-87	Color Macro 11
				88-95	Color Macro 12
				96-103	Color Macro 13
				104-111	Color Macro 14
		6	6	112-119	Color Macro 15
				120-127	Color Macro 16
				128-135	Color Macro 17
				136-143	Color Macro 18
				144-151	Color Macro 19
				152-159	Color Macro 20
				160-167	Color Macro 21
				168-175	Color Macro 22
				176-183	Color Macro 23
				184-191	Color Macro 24
				192-199	Color Macro 25
				200-207	Color Macro 26
				208-215	Color Macro 27
				216-223	Color Macro 28
				224-231	Color Macro 29
				232-239	Color Macro 30
				240-247	Color Macro 31
				248-255	Color Macro 32
					COLOR CHASE MACROS
				0	NO Function
				1-30	Chase Macro 1
				31-60	Chase Macro 2
				61-90	Chase Macro 3
				91-120	Chase Macro 4
				121-150	Chase Macro 5
				151-180	Chase Macro 6
				181-210	Chase Macro 7
				211-255	Chase Macro 8
					SHUTTER / STROBE
				0-31	LEDs OFF
				32-63	LEDs ON (NO STROBE)
				64-95	STROBE Effect SLOW to FAST
				96-127	LEDs ON (NO STROBE)
				128-159	STROBE Pulse Effect In Sequences
				160-191	LEDs ON (NO STROBE)
				192-223	Random STROBE Effect SLOW to FAST
				224-255	LEDs ON (NO STROBE)
					DIMMER INTENSITY / CHASE MACRO SPEED*
		5	8	0-255	*SPEED Control ONLY when in 12 CH Mode and the COLOR CHASE MACRO CHANNEL 7 DMX Value is (1-255)
					Intensity 0 to 100% / Speed SLOW to FAST
					DIMMING MODES
				0-20	STANDARD
				21-40	STAGE
				41-60	TV
				61-80	ARCHITECTURAL
				81-100	THEATER
		9	10	101-255	Default to Unit Setting

ELATION | VOLT Q5E™ | dmx traits

ELATION® VOLT Q5E™					
DMX Channel Values / Functions VERSION 2 (12 DMX Channels)					
Doc Date		2/6/2015		Soft Ver ≥1.0.3	
Specifications are subject to change without any prior written notice.					
MODE / CHANNEL				VALUE	FUNCTION
4 CH	5 CH	11 CH	12 CH		
		10	11		COLOR ENABLE
				0-189	NO Function
				190-255	Store WHITE BALANCE Enabled
					COLOR MODE
		11	12		NO Function
				0-189	NO Function
				190-254	EDIT a New WHITE BALANCE Value
				255	STORE a New WHITE BALANCE Value

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
 323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, Netherlands
 +31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu