

ELATION® 7 W PROFILE HP™

DMX Channel Values / Functions (4 DMX Channels)

Specifications are subject to change without any prior written notice.

MODE / CHANNEL		VALUE	FUNCTION
1CH	4CH		
1	1		DIMMER
		0-255	Intensity 0 to 100%
	2		DIMMER FINE
		0-255	FINE Intensity Adjustment
	3		STROBE
		0-31	LED OFF
		32-63	LED ON
		64-95	Strobe Effect SLOW to FAST
		96-127	LED ON
		128-159	Pulse Effect In Sequences
		160-191	LED ON
		192-223	Random Strobe Effect SLOW to FAST
	4		DIMMING CURVES
		0-20	STANDARD
		21-40	STAGE
		41-60	TV
		61-80	ARCHITECTURAL
		81-100	THEATRE
		101-255	Default to Unit Dimming Curve Setting

ELATION | CW PROFILE HP™ | dmx traits

**Elation Professional USA** | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | [www.elationlighting.com](http://www.elationlighting.com) | [info@elationlighting.com](mailto:info@elationlighting.com)

**Elation Professional B.V.** | Junostraat 2 | 6468 EW Kerkrade, Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | [www.elationlighting.eu](http://www.elationlighting.eu) | [info@elationlighting.eu](mailto:info@elationlighting.eu)