

# DTW BLINDER 700 IP™

SKU# DTW700



## Photometric Data

Specifications are subject to change without any prior written notice.

### 25° Beam Diameter with Fresnel Lens

	<b>3 m</b>	<b>9.8 ft</b>	<b>4 m</b>	<b>13.1 ft</b>	<b>5 m</b>	<b>16.4 ft</b>
<b>25° Beam Diameter</b>	1.33	4.4	1.77	5.8	2.21	7.3
	<b>lux</b>	<b>fc</b>	<b>lux</b>	<b>fc</b>	<b>lux</b>	<b>fc</b>
<b>WW LEDs 3,100K</b>	9,209	856	5,347	497	3,466	322
<b>AMBER LEDs 1,400K</b>	870	81	510	47	335	31
<b>FULL ON 2,940K</b>	9,390	872	5,486	510	3,549	330

### 78° Beam Diameter No Fresnel Lens

	<b>3 m</b>	<b>9.8 ft</b>	<b>4 m</b>	<b>13.1 ft</b>	<b>5 m</b>	<b>16.4 ft</b>
<b>78° Beam Diameter</b>	4.99	16.4	6.67	21.9	8.21	26.9
	<b>lux</b>	<b>fc</b>	<b>lux</b>	<b>fc</b>	<b>lux</b>	<b>fc</b>
<b>WW LEDs 3,100K</b>	1,432	133	883	82	602	56
<b>AMBER LEDs 1,400K</b>	110	10	80	7	49	5
<b>FULL ON 2,940K</b>	1,440	134	897	83	609	57