

**ELATION® DTW PAR 300™**  
**DMX Channel Values / Functions (8 DMX Channels)**

Features are subject to change without any prior written notice.

DMX CHANNEL MODE							VALUE	FUNCTION
01CH	03CH	04CH	05CH	06CH	07CH	08CH		
	1	1	1	1	1	1	0-255	<b>COOL WHITE - All LEDs</b> Cool White (0=Black - 255=100%)
	2	2	2	2	2	2	0-255	<b>WARM WHITE - All LEDs</b> Warm White (0=Black - 255=100%)
	3	3	3	3	3	3	0-255	<b>AMBER - All LEDs</b> Amber (0=Black - 255=100%)
1		4				4	0-255	<b>DIM TO WARM - All LEDs</b> 1,800K - 3,200K (0=Black - 255=100%)
					4	5		<b>SHUTTER / STROBE</b>
							0-31	NO Function
							32-95	Variable Strobe Effect SLOW to FAST
							96-127	LEDs ON
							128-159	Pulse Effect In Sequence SLOW to FAST
							160-191	LEDs ON
							192-223	Random Strobe Effect SLOW to FAST
						224-255	LEDs ON	
			4	4	5	6	0-255	<b>MASTER DIMMER</b> 0 to 100%
			5	5	6	7	0-255	<b>MASTER DIMMER FINE (16 bit)</b> 0 to 100%
					6	7		<b>DIMMING CURVE MODES</b>
							0-20	STANDARD
							21-40	STAGE
							41-60	TV
							61-80	ARCHITECTURAL
							81-100	THEATRE
						101-255	Default to Unit Setting	

**ELATION** | **DTW PAR 300™** | **dmx traits**

**Elation Professional USA** | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | [www.elationlighting.com](http://www.elationlighting.com) | [info@elationlighting.com](mailto:info@elationlighting.com)

**Elation Professional B.V.** | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | [www.elationlighting.eu](http://www.elationlighting.eu) | [info@elationlighting.eu](mailto:info@elationlighting.eu)