



REPORT

25800 COMMERCENTRE DRIVE, LAKE FOREST, CA 92630

Project No. G102697884

Date: August 22, 2016

REPORT NO. 102697884LAX-004

TEST OF ONE LED MOVING HEAD BEAM

MODEL NO. FUZE WASH RED ZOOM IN

RENDERED TO

ELATION LIGHTING
6122 S. EASTERN AVE
COMMERCE CA 90040

TEST: Electrical and Photometric tests as required to the IESNA test standard.

STATEMENT OF LIMITATION: This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the federal government.

AUTHORIZATION: The testing performed was authorized by signed quote number Qu-00648726.

STANDARDS USED: The following American National Standards or Illuminating Engineering Society of North America Test Guides were used in part or totally to test each specimen:

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

DESCRIPTION OF SAMPLE: The client submitted one production sample of model number FUZE WASH RED ZOOM IN. The sample was received by Intertek on August 11, 2016, in undamaged condition and one sample was tested as received. The sample designation was LAN1608110839-002.

DATES OF TESTS: August 16, 2016

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



SUMMARY

Model No.:	FUZE WASH RED ZOOM IN
Description:	LED Moving Head Beam

Criteria	Result
Total Lumen Output (Lumens)	219.5
Total Power (W)	42.69
Luminaire Efficacy (LPW)	5.142

EQUIPMENT LIST

Equipment Used	Model Number	Control Number	Last Date Calibrated	Calibration Due Date
LSI High Speed Mirror Goniometer	6440T	000943	08/15/16	09/15/16
Elgar Power Supply	CW1251	000944	VBU	VBU
Yokogawa Power Analyzer	WT210	000945	12/04/15	12/04/16
Temp. & RH Meter	971	001178	12/18/15	12/18/16
Extech Instruments Stop Watch	365510	001379	11/19/15	11/19/16
Tape Measure	C1-25	000915	12/04/15	12/04/16
Empire Magnetic Level	581-9	001610	VBU	VBU

TEST METHODS

Seasoning in Sample Orientation – LED Products

No seasoning was performed in accordance with IESNA LM-79.

Photometric and Electrical Measurements – Distribution Method

A LSI Type C High Speed Model 6440 Mirror Goniometer was used to measure the intensity (candelas) at each angle of distribution for each sample.

Ambient temperature was measured equal to the height of the sample mounted on the Goniometer equipment. Each sample was operated at input rated voltage in its designated orientation. Each sample was allowed to stabilize for at least thirty minutes before measurements were made. Electrical measurements including voltage, current, and power were measured using the Yokogawa Power Analyzer.

Some graphics were created with Photometrics Plus software.



RESULTS OF TEST (cont'd)


Photometric and Electrical Measurements at Ambient Temperature (25°C +/- 1°C) – Distribution Method

Intertek Sample No.	Base Orientation	Input Voltage {Vac}	Input Current (mA)	Input Power (Watts)	Input Power Factor	Absolute Luminous Flux (Lumens)	Lumen Efficacy (Lumens Per Watt)
LAN1608110839-002	UP	120.0	372.8	42.69	0.955	219.5	5.142

Intensity (Candlepower) Summary at 25°C - Candelas

Maximum Candela Value: 7,097.0

Angle	0	22.5	45	67.5	90
0	7039	7044	7045	7036	7070
5	1459	1494	1528	1577	1508
10	445	447	456	470	469
15	195	190	192	198	201
20	85	82	84	88	90
25	44	41	43	44	46
30	25	22	23	24	28
35	14	14	13	13	15
40	7	8	7	10	8
45	6	5	5	4	6
50	4	3	3	3	4
55	1	2	2	2	1
60	0	0	0	0	1
65	0	0	0	0	0
70	0	0	0	0	0
75	0	0	0	0	0
80	0	0	0	0	0
85	0	0	0	0	0
90	0	0	0	0	0



RESULTS OF TEST (cont'd)

Illumination Plots


Mounting Height: 10 ft.

Illuminance - Cone of Light

Illuminance at a Distance			
	Center Beam fc	Beam Width	
2.0ft	1,759.8 fc	0.2 ft	0.2 ft
4.0ft	439.9 fc	0.4 ft	0.4 ft
6.0ft	195.5 fc	0.6 ft	0.6 ft
8.0ft	110.0 fc	0.8 ft	0.8 ft
10.0ft	70.4 fc	1.0 ft	1.0 ft

■ Vert. Spread: 5.7°
■ Horiz. Spread: 6.0°

Isoillumination Plot



Zonal Lumen Summary and Percentages at 25°C

Zone	Lumens	% Luminaire
0-30	203.5	92.7
0-40	213.5	97.3
0-60	219.5	100.0
60-90	0.0	0.0
0-90	219.5	100.0
90-180	0.0	0.0
0-180	219.5	100.0

Zonal Lumens and Percentages at 25°C

Zone	Lumens	% Luminaire
0-10	125.4	57.1
10-20	55.8	25.4
20-30	22.3	10.2
30-40	10.0	4.6
40-50	4.5	2.0
50-60	1.5	0.7
60-70	0.0	0.0
70-80	0.0	0.0
80-90	0.0	0.0

PICTURE (not to scale)



CONCLUSION

The results tabulated in this report are representative of the actual test samples submitted for this report only. The data is provided to the client for further evaluation. Compliance to the referenced specification requirements was not determined in this report.

In Charge Of Tests:



Ameet Alawi
Technician
Lighting Division

Attachment: None

Report Reviewed By:



Melanie Brittain
Associate Engineer
Lighting Division