

Light efficiency:


3 Lumen/Watt

Light quality:

CRI: 0.0

Color temperature:

0 K



Product name:

Paladin

Test:


Zoom 50% Blue

Date:


5/1/2017

Output: 828 lm Power consumption: 238 W Peak: 7682 cd


Spectral distribution




Color coordinates



Zoom color point




CRI R values



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color divition from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0.0	0.0	0.0	0.0	0.0	0.154	0.024	0.207	0.049	n/a

Beam details



Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
18.2°	25.1°	31.1°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
7682 cd	0.9%	0.9%

Power

Power	Power factor	Power frequency
238 W	1.0	0 Hz

Nominal voltage	Voltage	Current
230 V	114 V	2.09 A

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
7676lx	1919lx	853lx	480lx	307lx	213lx	157lx	120lx	95lx	77lx	63lx	53lx	45lx	39lx	34lx	30lx	27lx	24lx	21lx	19lx
713.2fcd	178.3fcd	79.2fcd	44.6fcd	28.5fcd	19.8fcd	14.6fcd	11.1fcd	8.8fcd	7.1fcd	5.9fcd	5fcd	4.2fcd	3.6fcd	3.2fcd	2.8fcd	2.5fcd	2.2fcd	2fcd	1.8fcd