




Spectral distribution




Color coordinates



Zoom color point



CRI R values



Photometric Test Report


*Due to additional product enhancements, an updated version of this report may be available online. Please check www.elationlighting.com for the latest revision/update of this report.

Light Efficiency:



Output: 1520 lm

Light Quality:



Peak: 76149 cd

Color Temperature:




Power: 145 W

PF: 0.97

Beam Angle

5.7°



Product Name:

Fuze Par Z120

Test:

Zoom In Full On

Date:

6/3/2020


Note:




CIE 1931
x: 0.256
y: 0.200

Spectra



Dominant Wavelength: 425nm




Power



Color Details



TM30: 0.0



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0


CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

CRI: 0.0 (R1-R8)




CQS: 0.0



Color Parameters

Color Temperature	Color Rendering Index	Red Component	Color Fidelity	Color Gamut	Color Quality Scale	Color Coordinate CIE 1931	Color Coordinate CIE 1931	Color Coordinate	Color Coordinate	Color Deviation from Black Body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0.0	0.0	0.0	0.0	0.0	0.256	0.200	0.209	0.245	n/a

Beam Details



Beam Intensities from 1-20m

m	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
ft	3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6
lx	76134	19033	8459	4758	3045	2115	1554	1190	940	761	629	529	450	388	338	297	263	235	211	190
fcd	7073.1	1768.3	785.9	442.1	282.9	196.5	144.3	110.5	87.3	70.7	58.5	49.1	41.9	36.1	31.4	27.6	24.5	21.8	19.6	17.7

Intensities in 0° C-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	
76.1K	74.2K	56.5K	34.8K	18.4K	11.6K	7.0K	4.2K	2.1K	1.2K	0.8K	0.6K	0.5K	0.5K	0.4K	0.4K	0.3K	0.3K	0.3K	0.3K	0.2K
100%	97%	74%	46%	24%	15%	9%	5%	3%	2%	1%	1%	1%	1%	1%	0%	0%	0%	0%	0%	0%

Intensities in 90° C-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°	
76.1K	74.2K	56.5K	34.8K	18.4K	11.6K	7.0K	4.2K	2.1K	1.2K	0.8K	0.6K	0.5K	0.5K	0.4K	0.4K	0.3K	0.3K	0.3K	0.3K	0.2K
100%	97%	74%	46%	24%	15%	9%	5%	3%	2%	1%	1%	1%	1%	1%	0%	0%	0%	0%	0%	0%

Intensities in 180° C-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
76.1K	68.4K	54.9K	35.1K	19.4K	9.8K	5.2K	3.0K	1.9K	1.3K	1.0K	0.8K	0.7K	0.6K	0.6K	0.5K	0.4K	0.4K	0.3K	0.3K
100%	90%	72%	46%	26%	13%	7%	4%	3%	2%	1%	1%	1%	1%	1%	1%	1%	0%	0%	0%

Intensities in 270° C-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
76.1K	68.4K	54.9K	35.1K	19.4K	9.8K	5.2K	3.0K	1.9K	1.3K	1.0K	0.8K	0.7K	0.6K	0.6K	0.5K	0.4K	0.4K	0.3K	0.3K
100%	90%	72%	46%	26%	13%	7%	4%	3%	2%	1%	1%	1%	1%	1%	1%	1%	0%	0%	0%

Beam Angle 50%	Field Angle 10%	Cutoff Angle 2,5%	Intensity Ratio in 120° Cone	Intensity Ratio in 90° Cone
5.7°	11.3°	16.3°	88.4%	84.4%