



# PRISMA MINI PAR 20

## SPECIFICATIONS / TECHNICAL DATA REV A

### KEY FEATURES

IP65 Rated Exterior High-Power UV Wash Luminaire  
Scoop LED Reflector Design  
20 Degree Narrow Beam Angle  
365nm Peak True UV Wavelength  
Optional Black Glass Diffusion Filter



### SPECIFICATIONS

#### Dynamic Effects

- . 20° Beam Angle
- . Variable Dimming Curve Modes
- . High Speed Electronic Strobe
- . (7) 3W High Power UV Diode Led's
- . 20,000 Hour Average LED Life

#### Control

- . RDM (Remote DMX) Protocol Support
- . Art-Net Protocol Support
- . Master/Slave Modes
- . Onboard 4 Button Touch Control Panel

#### Connections

- . 9 ft (2.74m) 2-Conductor 14 Gauge IP Rated Power/Data Pigtail Cable Attached

#### Construction / Physical / Performance

- . Dimensions (LxWxH): in. 5.66 x 2.86 x 5.64 / 144 x 72.8 x 143.3 mm
- . Weight: 1.98 lbs. / 0.9kg

#### Electrical

- . Input Voltage: DC 0-25V
- . Current: 700 mA (Max)
- . Power Consumption: 18.7W
- . Voltage: 3.7V

MAGMATIC



# PRISMA MINI PAR 20

## SPECIFICATIONS / TECHNICAL DATA

### Certifications / Qualifications / Thermal

- . IP Rating: IP65 Rating
- . Approvals: ROHS, CE Approved
- . Cooling: Air Cooled
- . Maximum Temperature (Ambient): 113° F (45° C)
- . Minimum Temperature (Ambient): 14° F (-10° C)

### What's Included

- . Phoenix Connector (x1)
- . Positive Wire Tip Sheath (x1)
- . Negative Wire Tip Sheath (x1)

### Optional Accessories

- . Prisma Mini Par 20 Black Glass (PSG845)



MAGMATIC