



Acoustic Test Report

Test conditions

Test carried out according to ISO 3744:2010(E)

Device tested

Brand: _____

Model: _____

Serial #: _____

Software version: _____

Environment

Temperature: _____

Humidity: _____

Warm-up Time (mins): _____

Ambient Noise Level: _____

Fixture placement:

Fixture was placed at least one meter from walls and ceiling, as described in the Standard ISO 3744:2010(E)

Instrumentation

Instruments used

	Equipment	Make	Type
	Acoustic Analyser	NTI	XL2
	Audio Switch	Kramer	VS-4X
Measurement Microphones	Mic 01	NTI	M4261
	Mic 02	NTI	M4261
	Mic 03	NTI	M4261
	Mic 04	NTI	M4261

Setup

The product was placed in a semi-anechoic chamber (See figure 1). The ceiling, floor and walls were all acoustically absorbent. The main dimensions of the room were 4.15 m x 3.60 m x 3.30 m (Length x Width x Height)

FIGURE 01: TEST SETUP

The product was allowed a minimum of _____ minutes of warm-up time before measurements were performed.

Measurement method

Measurements were carried out using a setup with 4 microphones. The microphones were in turn moved to the measurement positions described below.

Measurement setup:

Microphone 01 is setup

Microphone 02 is setup

Microphone 03 is setup

Microphone 04 is setup

