

ELATION KL CYC L - DMX TRAITS

Dimmer 1Ch.	RGB 4Ch.	CCT 4Ch.	HSI 4Ch.	HSI EXT. 12Ch.	CMY 11Ch.	CMY EXT. 16Ch.	Std. 13Ch.	Ext. 20Ch.	Std. 2 Zone 19Ch.	Ext. 2 Zone 32Ch.	Ext. 4 Zone 31Ch.	Ext. 4 Zone 56Ch.	DMX Values	Function	Snap	Default Value
1	1	1	1	1	1	1	1	1	1	1	1	1	0-255	Dimmer Intensity 0 → 100%		0
		2	2	2	2	2	2	2	2	2	2	2	0-255	Dimmer Fine Fine Adjustment		0
														Shutter/Strobe		50
													0-31	Shutter closed		
													32-63	No function (shutter open)		
													64-95	Strobe effect slow to fast		
				3	3	3	3	3	3	3	3	3	96-127	No function (shutter open)		
													128-159	Pulse-effect in sequences		
													160-191	No function (shutter open)		
													192-223	Random strobe effect slow to fast		
													224-255	No function (shutter open)		
	2						4	4	4	4	4	4	0-255	Red 0 → 100%		0
								5		5		5	0-255	Red Fine Fine Adjustment		0
	3						5	6	5	6	5	6	0-255	Green 0 → 100%		0
								7		7		7	0-255	Green Fine Fine Adjustment		0
	4						6	8	6	8	6	8	0-255	Blue 0 → 100%		0
								9		9		9	0-255	Blue Fine Fine Adjustment		0
							7	10	7	10	7	10	0-255	Mint 0 → 100%		0
								11		11		11	0-255	Mint Fine Fine Adjustment		0
							8	12	8	12	8	12	0-255	Amber 0 → 100%		0
								13		13		13	0-255	Amber Fine Fine Adjustment		0
									9	14	9	14	0-255	Red 2 0 → 100%		0
										15		15	0-255	Red Fine 2 Fine Adjustment		0
									10	16	10	16	0-255	Green 2 0 → 100%		0
										17		17	0-255	Green Fine 2 Fine Adjustment		0
									11	18	11	18	0-255	Blue 2 0 → 100%		0
										19		19	0-255	Blue Fine 2 Fine Adjustment		0
									12	20	12	20	0-255	Mint 2 0 → 100%		0
										21		21	0-255	Mint Fine 2 Fine Adjustment		0
									13	22	13	22	0-255	Amber 2 0 → 100%		0
										23		23	0-255	Amber Fine 2 Fine Adjustment		0
											14	24	0-255	Red 3 0 → 100%		0
												25	0-255	Red Fine 3 Fine Adjustment		0

ELATION KL CYC L - DMX TRAITS

Dimmer 1Ch.	RGB 4Ch.	CCT 4Ch.	HSI 4Ch.	HSI EXT. 12Ch.	CMY 11Ch.	CMY EXT. 16Ch.	Std. 13Ch.	Ext. 20Ch.	Std. 2 Zone 19Ch.	Ext. 2 Zone 32Ch.	Ext. 4 Zone 31Ch.	Ext. 4 Zone 56Ch.	DMX Values	Function	Snap	Default Value
											15	26	0-255	Green 3 0 → 100%		0
												27	0-255	Green Fine 3 Fine Adjustment		0
											16	28	0-255	Blue 3 0 → 100%		0
												29	0-255	Blue Fine 3 Fine Adjustment		0
											17	30	0-255	Mint 3 0 → 100%		0
												31	0-255	Mint Fine 3 Fine Adjustment		0
											18	32	0-255	Amber 3 0 → 100%		0
												33	0-255	Amber Fine 3 Fine Adjustment		0
											19	34	0-255	Red 4 0 → 100%		0
												35	0-255	Red Fine 4 Fine Adjustment		0
											20	36	0-255	Green 4 0 → 100%		0
												37	0-255	Green Fine 4 Fine Adjustment		0
											21	38	0-255	Blue 4 0 → 100%		0
												39	0-255	Blue Fine 4 Fine Adjustment		0
											22	40	0-255	Mint 4 0 → 100%		0
												41	0-255	Mint Fine 4 Fine Adjustment		0
											23	42	0-255	Amber 4 0 → 100%		0
												43	0-255	Amber Fine 4 Fine Adjustment		0
					4	4							0-255	Cyan 0 → 100%		0
						5							0-255	Cyan Fine Fine Adjustment		0
					5	6							0-255	Magenta 0 → 100%		0
						7							0-255	Magenta Fine Fine Adjustment		0
					6	8							0-255	Yellow 0 → 100%		0
						9							0-255	Yellow Fine Fine Adjustment		0
			3	4									0-255	Hue 0 → 360°		255
			4	5									0-255	Saturation 0 → 100%		255

ELATION KL CYC L - DMX TRAITS

Dimmer 1Ch.	RGB 4Ch.	CCT 4Ch.	HSI 4Ch.	HSI EXT. 12Ch.	CMY 11Ch.	CMY EXT. 16Ch.	Std. 13Ch.	Ext. 20Ch.	Std. 2 Zone 19Ch.	Ext. 2 Zone 32Ch.	Ext. 4 Zone 31Ch.	Ext. 4 Zone 56Ch.	DMX Values	Function	Snap	Default Value
		3		6	7	10	9	14	14	24	24	44		Variable CCT		0
													0-23	Open		
													24-85	2400K → 8500K (See Sheet)		
													86-255	8500K		
									15	25	25	45		Variable CCT 2		0
													0-23	Open		
													24-85	2400K → 8500K (See Sheet)		
													86-255	8500K		
											26	46		Variable CCT 3		0
													0-23	Open		
													24-85	2400K → 8500K (See Sheet)		
													86-255	8500K		
											27	47		Variable CCT 4		0
													0-23	Open		
													24-85	2400K → 8500K (See Sheet)		
													86-255	8500K		
				7	8	11	10	15	16	26	28	48		CCT Cross Fade		0
													0	CCT		
													1-254	No Function		
													255	Color Mix		
				8	9	12	11	16	17	27	29	49		Color		0
													0	Open		
													1-179	Virtual Swatch Book (See Table)		
														Color Scroll		
													180-201	Clockwise Fast → Slow		
													202-207	Stop		
													208-229	Counter-clockwise Slow → Fast		
													230-234	Open		
														Random Slots		
													235-239	Fast		
													240-244	Medium		
													245-249	Slow		
													250-255	Open		
		4		9		13		17		28		50		Green Shift		0
													0	Idle		
													1-127	Full Minus Green to Neutral		
													128	Neutral White		
													129-255	Neutral to Full Plus Green		
										29		51		Green Shift 2		0
													0	Idle		
													1-127	Full Minus Green to Neutral		
													128	Neutral White		
													129-255	Neutral to Full Plus Green		
												52		Green Shift 3		0
													0	Idle		
													1-127	Full Minus Green to Neutral		
													128	Neutral White		
													129-255	Neutral to Full Plus Green		
												53		Green Shift 4		0
													0	Idle		
													1-127	Full Minus Green to Neutral		
													128	Neutral White		
													129-255	Neutral to Full Plus Green		
				10	10	14	12	18	18	30	30	54		EdgeLight Level		0
													0-10	Off		
													11-20	Default		
													21-255	Intensity Min → Max		

RELATION KL CYC L - DMX TRAITS

Dimmer 1Ch.	RGB 4Ch.	CCT 4Ch.	HSI 4Ch.	HSI EXT. 12Ch.	CMY 11Ch.	CMY EXT. 16Ch.	Std. 13Ch.	Ext. 20Ch.	Std. 2 Zone 19Ch.	Ext. 2 Zone 32Ch.	Ext. 4 Zone 31Ch.	Ext. 4 Zone 56Ch.	DMX Values	Function	Snap	Default Value
														Dim Modes		
													0-20	Standard		
													21-40	Stage		
													41-60	TV		
													61-80	Architectural		
													81-100	Theatre		
													101-120	Stage 2		
														Dimmer Delay Time		
													121	0s		
													122	0.1s		
													123	0.2s		
													124	0.3s		
													125	0.4s		
													126	0.5s		
													127	0.6s		
				11		15							128	0.7s	X	0
													129	0.8s		
													130	0.9s		
													131	1.0s		
													132	1.5s		
													133	2.0s		
													134	3.0s		
													135	4.0s		
													136	5.0s		
													137	6.0s		
													138	7.0s		
													139	8.0s		
													140	9.0s		
													141	10s		
													142-255	Idle		
														Control		
													0-69	Idle		
														EdgeLite Control		
													70-74	Disabled		
													75-79	Always ON		
													80-84	DMX		
													85-94	Red		
													95-99	Blue		
														Refresh Rate (Hz)		
													100	900		
													101	910		
													102	920		
													103	930		
													104	940		
													105	950		
													106	960		
													107	970		
													108	980		
													109	990		
													110	1000		
													111	1010		
													112	1020		
													113	1030		
													114	1040		
													115	1050		
													116	1060		
													117	1070		
													118	1080		
													119	1090		
													120	1100		

RELATION KL CYC L - DMX TRAITS

Dimmer 1Ch.	RGB 4Ch.	CCT 4Ch.	HSI 4Ch.	HSI EXT. 12Ch.	CMY 11Ch.	CMY EXT. 16Ch.	Std. 13Ch.	Ext. 20Ch.	Std. 2 Zone 19Ch.	Ext. 2 Zone 32Ch.	Ext. 4 Zone 31Ch.	Ext. 4 Zone 56Ch.	DMX Values	Function	Snap	Default Value
													121	1110		
													122	1120		
													123	1130		
													124	1140		
													125	1150		
													126	1160		
													127	1170		
													128	1180		
													129	1190		
													130	1200		
													131	1210		
													132	1220		
													133	1230		
													134	1240		
													135	1250		
													136	1260		
													137	1270		
													138	1280		
													139	1290		
													140	1300		
													141	1310		
													142	1320		
													143	1330		
													144	1340		
													145	1350		
													146	1360		
													147	1370		
				12	11	16	13	20	19	32	31	56	148	1380	X	0
													149	1390		
													150	1400		
													151	1410		
													152	1420		
													153	1430		
													154	1440		
													155	1450		
													156	1460		
													157	1470		
													158	1480		
													159	1490		
													160	1500		
													161	2500		
													162	4000		
													163	5000		
													164	6000		
													165	10000		
													166	15000		
													167	20000		
													168	25000		
													169-200	Idle		
														Dimmer Curves		
													201-210	Dimmer Curve: Linear (Default)		
													211-220	Dimmer Curve: Square		
													221-230	Dimmer Curve: Inverse Square		
													231-240	Dimmer Curve: S-Curve		
													241-255	Idle		