



THERMA TOUR 800

SPECIFICATIONS / TECHNICAL DATA REV A

KEY FEATURES

- 800 Watt low power consumption
- Over 30 hours of run time
- Haze lasting up to 3 hours after the machine is off
- Rugged mobile road case design
- Soundproof insulation for indoor use

DYNAMIC EFFECTS

- Output: 5600 cu.ft / Min
- External Visual Fluid Level Detection

COMPATIBLE FLUID

- Atmosity ARH (Oil based fluid)
- Atmosity AAH (Water based fluid)

CONSTRUCTION / PHYSICAL / PERFORMANCE

- External Visual Fluid Level Detection
- Fluid Tank Capacity: 2.5L
- Fluid Consumption: 1.5ml / Min.

CONTROL

- 2 Card Inputs
- RDM (Remote Device Management)
- Control Protocol: DMX
- DMX Control Modes: 2 (1 & 3 Channel)
- On-Board Timer Control
- 5 Factory Presets
- 4-Pin Wired Remote Input for optional remote
- Touch Screen Display
- Manual Control via on-board display

CONNECTIONS

- Data Connectors: 5-Pin XLR/Out, 4-Pin XLR Out
- Locking Power Connector

SIZE / WEIGHT

- Length: 24.45 in. (621.13mm)
- Width: 15.34 in. (389.63mm)
- Height: 19.87 in. (504.76mm - With Casters)
- Weight: 93 lbs. (42kg)

ELECTRICAL

- Power Consumption: 820w
- Input Voltage: 120V, 230V, 240V, 50 & 60Hz
- Breaker Size: 15A (120V version)
- Breaker Size: 10A (230V version)

THERMAL

- Maximum Temperature (Ambient): 104°F (40°C)
- Exterior Surface Temperature: 122°F (50°C)

WHATS INCLUDED

- Flight Case
- 14 AWG Locking Power Cable





THERMA TOUR 800

SPECIFICATIONS / TECHNICAL DATA REV A

OPTIONAL ACCESSORIES

MAGFLY Card

MAG-RF Card

Atmosity ARH (Oil base haze fluid)

Atmosity AAH (Water based fluid)

APPROVALS / RATINGS

CE | cETLus | IP20 | UKCA



621.13 mm
(224.45 in.)



389.63 mm
(15.33 in.)

504.76 mm
(19.87 in.)

MAGMATIC